

# FLEX ANGLES FROM MULTI-WALL



## Construction

Multi-Wall **Flex Angles** are **Angle Pads** constructed of laminated layers of 3/16" A flute single face corrugated paper built up to various thicknesses and lengths to meet or exceed National Motor Freight Specifications. These pads are pre-flexed allowing for normally rigid 90 degree **Angle Pads** to bend around curved products.

## Applications

These pre-flexed pads are shaped to conform to the perimeter of oval tables, round tables, or octagonal surfaces, as well as other products with unusual shaped surfaces.

## Available liners, widths, lengths, and thicknesses

The need for foam or polyethylene wrapping, and the labor to apply them to your product, can often be eliminated when **Flex Angles** are ordered with our non-abrasive liners. **Flex Angles** are available with standard corrugated liner or with optional non-abrasive linings: Michelman® coating, MULTI-SOFT tissue, or microfoam.

Face widths (the areas that contact the packaged product) are:

A = 2 1/2 x 2 1/2"

B = 2 x 2"

C = 3 x 3"

W = 4 x 4"

M = 5 x 5"

WA = 4 x 2 1/2"

WC = 4 x 3"

WX = 4 x 6"

Lengths are custom made and available up to 150".

Thicknesses for the **Flex Angle** can be made up to 5 ply.



[www.multiwall.com](http://www.multiwall.com)